

SELF-HOSTING > INSTALL & DEPLOY GUIDES >

Add rawManifest Files

View in the help center:
<https://bitwarden.com/help/add-rawmanifest-files/>

Add rawManifest Files

The Bitwarden self-host Helm Chart allows you to include other Kubernetes manifest files either pre- or post-install. To do this, update the `rawManifests` section of the chart.

Traefik IngressRoute example

For example, to install Traefik's IngressRoute as an alternative to Kubernetes' Ingress controller, add the following:

Note

In this example, you would also need to disable the ingress controller at `general.ingress.enabled`: within your `my-values.yaml` file.

Bash

```
rawManifests:
  preInstall: []
  postInstall:
  - apiVersion: traefik.containo.us/v1alpha1
    kind: Middleware
    metadata:
      name: "bitwarden-self-host-middleware-striprefix"
    spec:
      stripPrefix:
        prefixes:
          - /api
          - /attachments
          - /icons
          - /notifications
          - /events
          - /scim
          ##### NOTE: Admin, Identity, and SSO will not function correctly with path strip middlew
are
  - apiVersion: traefik.containo.us/v1alpha1
    kind: IngressRoute
    metadata:
      name: "bitwarden-self-host-ingress"
    spec:
      entryPoints:
        - websecure
      routes:
        - kind: Rule
          match: Host(`REPLACEME.COM`) && PathPrefix(`/`)
          services:
            - kind: Service
              name: bitwarden-self-host-web
              passHostHeader: true
              port: 5000
        - kind: Rule
          match: Host(`REPLACEME.COM`) && PathPrefix(`/api/`)
```

```
services:
  - kind: Service
    name: bitwarden-self-host-api
    port: 5000
middlewares:
  - name: "bitwarden-self-host-middleware-striprefix"
- kind: Rule
  match: Host(`REPLACEME.COM`) && PathPrefix(`/attachments/`)
  services:
    - kind: Service
      name: bitwarden-self-host-attachments
      port: 5000
  middlewares:
    - name: "bitwarden-self-host-middleware-striprefix"
- kind: Rule
  match: Host(`REPLACEME.COM`) && PathPrefix(`/icons/`)
  services:
    - kind: Service
      name: bitwarden-self-host-icons
      port: 5000
  middlewares:
    - name: "bitwarden-self-host-middleware-striprefix"
- kind: Rule
  match: Host(`REPLACEME.COM`) && PathPrefix(`/notifications/`)
  services:
    - kind: Service
      name: bitwarden-self-host-notifications
      port: 5000
  middlewares:
    - name: "bitwarden-self-host-middleware-striprefix"
- kind: Rule
  match: Host(`REPLACEME.COM`) && PathPrefix(`/events/`)
  services:
    - kind: Service
      name: bitwarden-self-host-events
      port: 5000
  middlewares:
```

```
- name: "bitwarden-self-host-middleware-striprefix"
- kind: Rule
  match: Host(`REPLACEME.COM`) && PathPrefix(`/scim/`)
  services:
    - kind: Service
      name: bitwarden-self-host-scim
      port: 5000
  middlewares:
    - name: "bitwarden-self-host-middleware-striprefix"
##### NOTE: SSO will not function correctly with path strip middleware
- kind: Rule
  match: Host(`REPLACEME.COM`) && PathPrefix(`/sso/`)
  services:
    - kind: Service
      name: bitwarden-self-host-sso
      port: 5000
##### NOTE: Identity will not function correctly with path strip middleware
- kind: Rule
  match: Host(`REPLACEME.COM`) && PathPrefix(`/identity/`)
  services:
    - kind: Service
      name: bitwarden-self-host-identity
      port: 5000
##### NOTE: Admin will not function correctly with path strip middleware
- kind: Rule
  match: Host(`REPLACEME.COM`) && PathPrefix(`/admin`)
  services:
    - kind: Service
      name: bitwarden-self-host-admin
      port: 5000
tls:
  certResolver: letsencrypt
```