PASSWORD MANAGER > AUTOFILL >

Autofill Custom Fields

Weergeven in het Helpcentrum: https://bitwarden.com/help/auto-fill-custom-fields/

U bitwarden

Autofill Custom Fields

Bitwarden can do more than just autofill your usernames and passwords! Bitwarden browser extensions can autofill custom fields to simplify filling in security questions, PINS, and more.

Additionally, if your browser extension is having issues autofilling usernames and passwords for a particular site, using linked custom fields can force an autofill.

∂ Tip

It's important to name the custom field correctly in order for autofill to work. Learn more.

To autofill custom fields:

- 1. Open the browser extension to the **Vault** view. This view automatically detects the website (for example, myverizon.com) of the page displayed in the open tab and surfaces any logins with corresponding URIs.
- 2. Select the Fill button on item that contains the custom field you want to autofill:

	Vault		+ New	Ø	FS	Q	ß
	Q Se	arch			I		
	Vau	der V	Collection Type		$\overline{}$		
	Autofill	suggestions	_		1		
e.g. 'cats playing keyboards'		Custom Field Autofill	Fill	٦	:		
	All item	IS			20		
	X B	Company Twitter Accour	nt 🖸	Ū	:		
	B Identity for Company Shipping Brett Warden Item to Assign myusername Item with 2E4 ■		Ū	:	-		
			Ū	:			
			_		ļ		
	F Vault	C Generator	⊲ Send	ई Sett	्रे ings		

Item with a custom field

The browser extension will find any fields that match the custom field name and autofill that field's value.

U bitwarden

Using linked custom fields

Linked custom fields can be used to solve issues where your browser extension can't autofill usernames and passwords for a particular site. To create and autofill a linked custom field:

- 1. In the Custom fields section of an item's Edit panel, choose Linked from the Field type dropdown.
- 2. In the **Name** input, give the custom field a name that corresponds to the username or password's HTML form element id, name, aria-label, or placeholder.

∏ Tip

You can get the right value by right-clicking the form element and using the Copy Custom Field Name context menu option:



3. Select Add.

- 4. Select **Username** or **Password** for the field's value depending on which credential you are having trouble autofilling. In many cases, you'll need to create a linked custom field for each.
- 5. Save the changes to the vault item.

Now that you have created one or more linked custom fields, you can autofill using the method described in an earlier section. When you do, your browser extension will autofill the username, password, or both into the HTML form element given for a field Name.

U bit warden

Special autofill scenarios

HTML

Typically custom fields are autofilled in HTML <form> or <input> elements, however Bitwarden browser extensions can autofill custom field values into the innerText of HTML elements as well.

In order to autofill into a element, the opening tag must have the data-bwautofill attribute. So, in the following scenario:

Bash

Bitwarden is great.

A custom field with name: myspan will replace Bitwarden is great with whatever is saved in the custom field's value.