

SJÄLVHOTELL > INSTALLATIONS- OCH DISTRIBUTIONSGUIDER >

Lägg till rawManifest-filer

View in the help center:
<https://bitwarden.com/help/add-rawmanifest-files/>

Lägg till rawManifest-filer

Bitwarden själv-värd Helm Chart låter dig inkludera andra Kubernetes manifestfiler antingen före eller efter installation. För att göra detta, uppdatera avsnittet `rawManifests` i diagrammet.

Traefik IngressRoute exempel

Till exempel, för att installera Traefiks IngressRoute som ett alternativ till Kubernetes Ingress-kontroller, lägg till följande:

Note

In this example, you would also need to disable the ingress controller at `general.ingress.enabled`: within your `my-values.yaml` file.

Bash

```
rawManifests:
  preInstall: []
  postInstall:
    - apiVersion: traefik.containo.us/v1alpha1
      kind: Middleware
      metadata:
        name: "bitwarden-self-host-middleware-striprefix"
      spec:
        stripPrefix:
          prefixes:
            - /api
            - /attachments
            - /icons
            - /notifications
            - /events
            - /scim
            ##### NOTE: Admin, Identity, and SSO will not function correctly with path strip middlew
are
    - apiVersion: traefik.containo.us/v1alpha1
      kind: IngressRoute
      metadata:
        name: "bitwarden-self-host-ingress"
      spec:
        entryPoints:
          - websecure
        routes:
          - kind: Rule
            match: Host(`REPLACEME.COM`) && PathPrefix(`/`)
            services:
              - kind: Service
                name: bitwarden-self-host-web
                passHostHeader: true
                port: 5000
          - kind: Rule
            match: Host(`REPLACEME.COM`) && PathPrefix(`/api/`)
```

```
services:
  - kind: Service
    name: bitwarden-self-host-api
    port: 5000
middlewares:
  - name: "bitwarden-self-host-middleware-stripprefix"
- kind: Rule
  match: Host(`REPLACEME.COM`) && PathPrefix(`/attachments/`)
  services:
    - kind: Service
      name: bitwarden-self-host-attachments
      port: 5000
  middlewares:
    - name: "bitwarden-self-host-middleware-stripprefix"
- kind: Rule
  match: Host(`REPLACEME.COM`) && PathPrefix(`/icons/`)
  services:
    - kind: Service
      name: bitwarden-self-host-icons
      port: 5000
  middlewares:
    - name: "bitwarden-self-host-middleware-stripprefix"
- kind: Rule
  match: Host(`REPLACEME.COM`) && PathPrefix(`/notifications/`)
  services:
    - kind: Service
      name: bitwarden-self-host-notifications
      port: 5000
  middlewares:
    - name: "bitwarden-self-host-middleware-stripprefix"
- kind: Rule
  match: Host(`REPLACEME.COM`) && PathPrefix(`/events/`)
  services:
    - kind: Service
      name: bitwarden-self-host-events
      port: 5000
  middlewares:
```

```
- name: "bitwarden-self-host-middleware-striprefix"
- kind: Rule
  match: Host(`REPLACEME.COM`) && PathPrefix(`/scim/`)
  services:
    - kind: Service
      name: bitwarden-self-host-scim
      port: 5000
  middlewares:
    - name: "bitwarden-self-host-middleware-striprefix"
##### NOTE: SSO will not function correctly with path strip middleware
- kind: Rule
  match: Host(`REPLACEME.COM`) && PathPrefix(`/sso/`)
  services:
    - kind: Service
      name: bitwarden-self-host-sso
      port: 5000
##### NOTE: Identity will not function correctly with path strip middleware
- kind: Rule
  match: Host(`REPLACEME.COM`) && PathPrefix(`/identity/`)
  services:
    - kind: Service
      name: bitwarden-self-host-identity
      port: 5000
##### NOTE: Admin will not function correctly with path strip middleware
- kind: Rule
  match: Host(`REPLACEME.COM`) && PathPrefix(`/admin`)
  services:
    - kind: Service
      name: bitwarden-self-host-admin
      port: 5000
tls:
  certResolver: letsencrypt
```